## 5-1508 Steep Slope Standards

**Comment:** Section 5-1508, "Steep Slope Standards," amends existing Section 5-1508 in the General Development Standards Chapter of the Zoning Ordinance. During Phase Two, we recommend this section be folded into a new "Environmental Protection Standards" chapter. It will remain separate from MDOD and RSCOD standards since the County does contain steep and moderately steep slope areas outside of these overlay districts; however where the MDOD covers steep slopes, the steep slope standards shall apply.

*Table of Contents included for review purposes only.* 

(A)	PURPOSE AND INTENT
(B)	APPLICABILITY AND EXEMPTIONS2
(C)	ESTABLISHMENT OF STEEP SLOPE AREAS2
(D)	PERMITTED USES AND ACTIVITIES4
(E)	DEVELOPMENT STANDARDS
	(A) <b>Purpose and Intent.</b> Loudoun County's General Plan policies recognize that improper uses and disturbance in steep slope areas cause erosion, result in structural failure of structures and roads, and lead to downstream flooding and other hazards. Development in these areas also requires

that improper uses and disturbance in steep slope areas cause erosion, result in structural failure of structures and roads, and lead to downstream flooding and other hazards. Development in these areas also requires higher volumes of cut and fill and greater removal of vegetation than on flatter lands. The provisions in this section, including a prohibition of development on steep slope areas greater than 25% and limitations on development on moderately steep slope areas from 15% to 25%, are intended to reasonably implement the General Plan policies, and more specifically promote the following:

(1) Undertake development in a manner that will protect life and property from hazards due to slope, unstable and erodible soils, earth movement, and other geologic and hydrologic hazards;

 (2) Reduce potential for increased erosion, sedimentation, and surface runoff and the resulting adverse impacts on water quality;

 (3) Promote a safe means of ingress and egress for vehicular and pedestrian traffic in sloped areas;

(4) Preserve the visual quality of steep slope areas, which are a valuable natural and economic resource to the County; and

1 2		(5)	Encourage innovative and imaginative building techniques to create structures and site plans that are suited to sloped terrain.
3	(B)	Appli	cability and Exemptions
4		(1)	Applicability.
5 6 7 8 9 10 11 12			(a) General Rule. Except as exempted in (B) below, this section shall apply to all land disturbing activity, including new development and subdivision, proposed on properties or the areas of properties containing "moderately steep slope areas" or "steep slope areas," as those terms are defined in Section 5-1508(C)(2) below and as shown on the Loudoun County Soils Map, as amended from time-to-time by the County Soil Scientist, and as shown on the Loudoun County Steep Slopes Map.
14 15 16 17 18 19 20 21			(b) Steep Slopes in the RSCOD/Conflicting Provisions. This section shall apply to moderately steep slope areas or steep slope areas, as defined in Section 5-1508(C)(2) below, that are located within a Protected River and Stream Corridor subject to Section 4-2000, River and Stream Corridor Overlay District (RSCOD). However, to the extent that the standards in this Section 5-1508 conflict with provisions in the RSCOD (Section 4-2000), the standard that affords the steep slopes the greater level of protection shall apply.
23 24 25 26 27 28		(2)	Note re. Exemptions. The extent and type of exemptions, if any, are discussed in the vested rights section of Clarion Associates Annotated Outline of Proposed Land Use Regulations for Loudount County. This subsection on exemptions will be drafted at a later time according to the direction received after discussion and public input on the annotated outline.
29	(C)	Estab	lishment of Steep Slope Areas
30 31 32 33 34 35		(1)	County Mapping as Resource. The County Soils Map and Steep Slopes Map shall be used as the source of delineation of sloped areas and related unstable soils. A field-prepared or aerial topographic survey of greater accuracy (2 feet or smaller contour interval), certified by a licensed surveyor or engineer and approved by the County, may also be used.

1 2	(2)			of Steep Slope Areas. Steep slope areas are one of the following two different categories:
3 4 5 6		(a)	slope a	rately Steep Slope Areas. This category of steep area includes only land areas with slopes from 15% to identified as slope Class D on Loudoun County Soils
7 8 9 10			(i)	Land areas that have moderately steep slopes (15% to 25%), together with unstable soils, are categorized as "Steep Slope Areas" under subsection (b) below.
11 12 13		(b)	includ	<b>Slope Areas.</b> This category of steep slope area es land areas with either of the following teristics:
14 15			(i)	Slopes greater than 25% (identified as slope Class E on Loudoun County Soils Map); or
16 17 18 19 20 21			(ii)	Moderately steep slopes, as defined in (a) above, together with Unstable Soils including the following soil series: Morven (soil mapping unit 13), Airmont (units 27 and 59), Lew (unit 88), and Springwood (units 90 and 91), as described in the Interpretive Guide to the Use of Soils Maps in Loudoun County.
22 23 24 25 26 27	(3)	only aparea. If the ste	pply if the state of the state	ze of Steep Slope Area. This Section 5-1508 shall the steep slope area exceeds 5,000 square feet in land poses of this provision, the entire contiguous area of es shall be included in the minimum size calculation, the number of individual lots or different land volved.
28 29 30 31 32		(LSDC) steep s hinder	D) to st slope ar compl	mend Land Subdivision and Development Ordinance ate that "applicants shall avoid laying out lots in reas that do not contain sufficient buildable area and iance with the provisions of Section 5-1508, Steepeds, of the Zoning Ordinance."
33 34				

1	(D)	Perm	mitted Uses and Activities.		
2		(1)	Steep	Slope Areas	
3 4 5			(a)	<b>Applicability.</b> This subsection (D)(1) applies to lands with Steep Slope Areas, as defined in subsection (C)(2)(b), above.	
6 7 8 9 10			(b)	General Prohibition on Land Disturbance. Land disturbing activities, including but not limited to clearing, excavation, grading, construction, reconstruction, and investigative land disturbing activities such as test wells, are prohibited on any Steep Slope Area, except as allowed under subsections (c) and (d) below.	
12 13 14			(c)	<b>Permitted Uses and Activities.</b> The following uses are permitted on Steep Slope Areas, subject to the applicable development standards in Section (E) below:	
15				(i) Agriculture;	
16 17				(ii) Silviculture uses, subject to a Forest Management Plan;	
18				(iii) Passive recreation uses, including trails; and	
19				(iv) Open space, and other conservation uses.	
20 21				(v) Limited land disturbing activity for the sole purpose of surveying and land investigation.	
22 23 24 25 26 27 28			(d)	Special Exception Uses and Activities. The County may permit minor utilities and driveways on Steep Slope Areas when no feasible alternative exists, subject to Section 6-1300, Special Exceptions. All applicable development standards in the Facilities Standards Manual, and the requirements under subsection (E)(4), Roads and Driveway Standards, below, shall apply.	
29		(2)	Mode	erately Steep Slope Areas	
30 31 32			(a)	<b>Applicability.</b> This subsection (D)(1) applies to lands with Moderately Steep Slope Areas, as defined in subsection (C)(2)(a), above.	
33 34 35			(b)	<b>Permitted Uses and Activities.</b> Notwithstanding uses otherwise allowed by the applicable underlying zoning district, the only principal uses allowed on Moderately	

1 2	Steep Slope Areas shall be the following, subject to the applicable development standards in Section (E) below:
3	(i) Agriculture;
4 5	(ii) Silviculture activities, subject to a Forest Management Plan;
6 7	(iii) Single-family detached residential uses (including related drainfields);
8	(iv) Passive recreation uses;
9	(v) Open space, and other conservation uses;
10 11	(vi) Limited land disturbing activity for the sole purpose of surveying and land investigation; and
12 13 14	(vii) Minor utilities, roads and driveways, subject to standards in the Facilities Standards Manual and in subsection (E)(4), below.
15 16 17 18 19	(c) Special Exception Uses on Moderately Steep Slope Areas. The County may permit the following special exception uses on Moderately Steep Slope Areas, subject to Section 6-1300, Special Exceptions, and subject to all applicable development standards in Section (E) below:
20	(i) Subdivisions with three (3) or more lots; and
21	(ii) Cluster subdivisions.
22 23 24 25 26 27	(E) <b>Development Standards.</b> Development and uses on steep slope areas shall take into account the way in which land use planning, soil geology, hydrology, civil engineering, environmental design, architectural and landscape design, and related disciplines are applied. At a minimum, development on steep slope areas shall comply with the guidelines in the Facilities Standards Manual and the following standards.
28 29	<b>Comment:</b> Some of the following standards may be included as part of the Facilities Standards Manual during Phase 2 of this project.
30 31	(1) <b>Grading Standards</b> . The applicant shall preserve natural landforms and minimize grading and other land disturbance.
32 33 34	(a) <b>Cutting to Create Benches.</b> Cutting and grading to create benches or pads for additional or larger building sites shall be avoided to the maximum extent feasible.

1 2 3 4	(b)	grade (4) fee	s on Changing Natural Grade. The original, natural of a lot shall not be raised or lowered more than four at any point for the construction of any structure or vements, except:
5 6 7 8 9		(i)	The lot's original grade may be raised or lowered a maximum of six (6) feet if retaining walls are used to reduce the steepness of man-made slopes, provided that the retaining walls comply with the requirements set forth in this Section.
10 11 12		(ii)	As necessary to construct a driveway from the road to a garage or parking area, grading changes or retaining walls up to 6 feet may be allowed
13 14		(iii)	The County may approve other exceptions to this standard if it finds that the proposal:
15			1. Is consistent with the intent of this Section;
16 17			2. Offers an exemplary design that preserves the natural land form; and
18 19 20 21			3. Results in less total site disturbance than would compliance with the maximum limits on changing natural grade stated in this subsection.
22 23 24 25 26	(c)	Separa structu swimn	ng for Accessory Building Pads Discouraged. Ite building pads for accessory buildings and tres other than private garages, such as tennis courts, ning pools, outbuildings, and similar facilities, shall couraged on moderately steep slope areas.
27	(d)	Limits	s on Man-Made Slopes
28 29		(i)	Man-made slopes shall not exceed 25% or a height of 50 feet.
30 31 32		(ii)	The County may allow exceptions to slope and height requirements for man-made slopes in (d)(i) related to the following activities:
33			1. Highway noise attenuation;
34			2. Embankments for reservoirs; and
35			3. Road embankments.
36 37 38		(iii)	All cut, filled, and graded slopes shall be recontoured to the natural, varied contour of the surrounding terrain.

1 2 3	(2)	footing	gs and i	To the maximum extent feasible, excavation for foundations shall be limited to lessen site disturbance impatibility with sloped terrain.
4 5 6 7	(3)	the ste	epness cive to	falls. Use of retaining walls is encouraged to reduce of man-made slopes and to provide planting pockets o vegetation, with adherence to the following
8 9		(a)		ning walls shall not exceed four (4) feet in height from hished grade, except for:
10 11			(i)	A structure's foundation wall (i.e., a retaining wall may be part of a permitted dwelling unit);
12 13			(ii)	As necessary to construct a driveway from the street to a garage or parking area; and
14			(iii)	As otherwise expressly allowed by this Section.
15 16		(b)	In no height	case shall a retaining wall exceed six (6) feet in
17 18 19 20		(c)	Count number	eing shall be limited to two tiers, except that the y may approve more than two tiers when a greater er of tiers will result in less land disturbance and less man-made slopes.
21 22 23			(i)	The width of the terrace between any two vertical retaining walls shall be at least five (5) horizontal feet.
24 25 26			(ii)	Terraces created between retaining walls shall be permanently landscaped or revegetated pursuant to Landscaping Standards in Section 5-1300.
27 28		(d)		ning walls shall be faced with stone or earth-colored ials similar to the surrounding natural landscape.
29	(4)	Roads	and D	riveway Standards
30 31 32		(a)		ads and driveways and other vehicular access routes follow natural contour lines to the maximum extent le.
33 34 35 36		(b)	cross allowe	ads, driveways, or other vehicular access routes shall steep slopes greater than 50%, except driveways as ed by Section 5-1508(D)(1)(d), "Special Exception and Activities [on Steep Slope Areas]."

1 2 3 4		(c)	Roads shall not be constructed on steep slopes of 25% or greater, unless no other feasible alternative exits to access a legal lot of record approved prior to the effective date of this Section.
5 6 7 8 9 10 11 12		(d)	Driveways and other vehicular routes used to access a parcel shall not be allowed to cross slopes between 25% and 50%, except driveways as allowed by Section 5-1508(D)(1)(d), "Special Exception Uses and Activities [on Steep Slope Areas]." In addition, the County may allow a short run of no more than 100 feet or 10% of the driveway's entire length, whichever is greater, based on a geotechnical study and findings that:
13 14 15			(i) In no case shall any short run exceed 100 feet or 10% of the entire length of the driveway, whichever is greater; and
16 17 18 19 20			(ii) Such driveway will not have significant adverse visual, environmental or safety impacts, or appropriate engineering or other measures will be taken by the developer to substantially mitigate any such adverse impact; and
21 22			(iii) No alternative location for access is feasible or available.
23 24 25		(e)	The County encourages shared driveways to reduce land disturbance, provided that shared driveways are placed in an easement.
26 27 28		(f)	The centerline grade of private roads and driveways shall comply with applicable standards stated in the Loudoun County Facilities Standards Manual.
29 30 31		(g)	Storm drainage and culvert design shall conform to the requirements of the Loudoun County Facilities Standards Manual.
32 33 34 35	(5)	develo or rev	lopment on moderately steep slope areas shall be landscaped vegetated pursuant to the standards and provisions set forth in ion 5-1300, Landscaping, Buffering and Tree Preservation.
36 37 38 39	(6)	incorp and en	mwater Best Management Practices. The applicant shall reporate stormwater management Best Management Practices erosion and sediment control practices, as required by Chapter the Facilities Standards Manual and such practices shall be

## Public Review Draft

1 2 3 approved by the Department of Building and Development prior to issuance of a zoning permit. (Note: Existing requirement with minor text changes).